line worker 250 – compatible jetting units + extensions

z0000802 rotation kit 30, 380 vc, 3000 bar, e-drive

z0000931 rotation kit 10, 380 vp, 1000 bar, e-drive

z0000801 rotation kit 5, 380 vp, 500 bar, e-drive

z0000910 line pointer

z0000573 pointspeed reg. 30, 4/2, 3000 bar + **z0000758** holder

z0000835 rotation kit 30, 150, 3000 bar, self-drive + **z0000758** holder

z0000952 oscillation kit 30, cage, 3000 bar, e-drive

z0000936 jet cap 370/430, oscillation

z0000914 holder corner works



also available in widths up to 150 mm

variable widths and types of jetting tools for removal marking lines

optional accessories

e1000136

e1210196

e1210132

z0000993

line worker 250

	max. 3000 bar (max. 43500 psi)
	45 l/min (max. 3000 bar) 85 l/min (max. 1500 bar)
	max. 970 N (97 kg)
	e-drive wheels, rpm controlled e-drive nozzles, rpm controlled
	230 V / 50 Hz, 16 A
IP	55
	24/1 h/d
	24 months
	120 kg
	1510 × 577 × 1110 mm
rent	✓
n°	z0000683 (standard version)

services

falch gmbh
headquarter
street of water jetting 1
89143 blaubeuren-seissen (germany)
+49 7344 9244-0
+49 7344 9244-4090
info@falch.com
www.falch.com

v0000683/10.03.2022

robotics

line worker 250

www.falch.com

examples



high-end water jetting tool for perfect surface preparation

falch®
world of water jetting

standard version

- perfect surface quality
- high working speed
- dry surface thanks to vacuum system

e-drive for jetting unit

e-drive for wheels

vacu press for waste water

crane hook

mega seal

brush seal (optional)

nozzle check

emergency button

ground adaptation

line pointer for less double jetting

user-friendly height adjustment


additional weights

*pictured products are subject to change, nonliability for picture true delivery.